


# Mini bleeder valve

stainless steel, not type-tested

**STAINLESS STEEL**

Art. No. 103916

Type No. 218.11-ES



Exemplary illustration

Manual adjustment of the blow-off pressure (lock nut).

For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.


## Technical data

Operating pressure	0.5 - 60 bar
Operating temperature	-20 to 180 °C
Set pressure	1 - 4 bar
Material	Stainless steel 1.4305
Sealant	FKM 75, 75+-5 Sh.A black, thickness of 2 mm
Spring	Stainless steel 1.4310
Max. blow-off rate	200 l/min
Thread	G 1/8
C	27.0 mm
D	7.0 mm
a/f	16 mm
do	3.0 mm

## Commercial data

Customs tariff number	84814010
Country of origin	DE
eCl@ss 5.1.4	27292490
eCl@ss 9.0	27292490
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

## Dimensions



Thread	C mm	D mm	a/f mm	SW 1 mm	Female thread mm	do mm
G 1/8	27.0 - 34.0	7.0	16	14	M12x1	3.0