

Storz reducer

stainless steel V4A

STAINLESS STEEL

Art. No. 108351

Type No. 3406.8965



Exemplary illustration

High-quality series in V4A stainless steel. For quick and simple hose connections. User friendly, the coupling elements are joined without damaging the seal. Applications: Industrial plant engineering, shipbuilding, chemical industry.

Technical data

Material	stainless steel V4A
Sealant	FKM
Max. operating pressure	16 bar
Operating temperature	-15 to 200 °C
Storz size	75-B
Lug distance 1	89 mm
Flange	DN 65
Hole circle dia.	145 mm
No. of bolt holes	4
Weight	4.4 kg

Commercial data

Customs tariff number	73072980
Country of origin	DE
eCl@ss 5.1.4	40040405
eCl@ss 9.0	40040405
UNSPSC_Code_v190501	46191603
UNSPSC_CodeDesc_v190501	Fire hoses or nozzles

Material informations

REACH SVHC1 substance name	no
CAS no. SVHC 1	no CAS No.
RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Accessories

	Art. No.	Type No.
Spanner for Storz coupling, for tappet distance 66, 89, 133	108273	2408.700

Spareparts

	Art. No.	Type No.
Replacement seal for Storz coupling, made of FKM, Storz size 75-B	108367	3408.89