


# Stopper valve, straight push-in fitting

»blue series«

EASY

Art. No. 110178 Type No. 196.3810



Exemplary illustration

The air supply is completely shut off as soon as the hose is disconnected from the union. The flow rate is only guaranteed if the hose is securely inserted.

Discontinued product. No longer available. New product151457 (196.3810-2)

## **Technical data**

Working pressure	0 - 10 bar			
Temperature range	0 to 60 °C			
Series	Blue series			
Material	Plastic and nickel-plated brass			
Medium	Compressed air			
Sealant	NBR			
Sleeve	Plastic blue			
Applications	Compressed air systems			
Recommended hose	PU or PA (nylon)			
Function	Self-locking			
Thread form	Conical male thread			
Standard thread	ISO 7-1			
Version	PTFE coated			
Thread	R 3/8			
For tube O.D.	10 mm			
L1	37.0 mm			
a/f	17 mm			

The suitability test for the use with alternative specifications is the user's responsibility.




## **Commercial data**

Customs tariff number	39174000
Country of origin	CN
eCl@ss 5.1.4	27294201
eCl@ss 9.0	27294201
UNSPSC_Code_v190501	27131613
UNSPSC_CodeDesc_v190501	Air coupling

### **Material informations**

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

### Dimensions



Thread	Standard thread	For tube O.D.	F	a/f	L1	D1
		mm	mm	mm	mm	mm
R 3/8	ISO 7-1	10	10.5	17	37.0	17.0