

Handheld tyre gauge

MAX

Art. No. 114523

Type No. 34.012



Exemplary illustration

These pressure gauges are effectively protected against shock and impact by means of a free-standing plastic cap. They can be loaded against gauge pressure and up to the maximum scale value.
With push-in plug for DN 7.2 coupling.

Discontinued product. No longer available. New product 205570 (34.013.2)

Technical data

Version	with clip-on connector
Measuring range	0 to 4 bar
Measuring range	0 - 56 psi
Description	uncalibrated
Hose connection	G 1/4, swivelling
Hose length	50 cm

Commercial data

Customs tariff number	90262080
Country of origin	DE
eCl@ss 5.1.4	27200610
eCl@ss 9.0	27200610
UNSPSC_Code_v190501	41103311
UNSPSC_CodeDesc_v190501	Manometers

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Product informations

Single-lever operation: Inflation, deflation and checking with a single handle

To check: lever in home position

To deflate: lever actuated half-way

To inflate: lever fully actuated

Pressure gauge: Ø 80 mm, horizontal operating position, overpressure-proof up to 16 bar, PE protective cap

Operating temperature: -10 to 60 °C

Lever plug and double-sided service station plug: For all tire valves with valve thread VG 8 (cars, trucks, motorcycles), in offset design, especially for dual tires and motorcycles

Also suitable for tire gas (nitrogen)

Accessories

	Art. No.	Type No.
Multi purpose nozzle set, inserting into the momentary plug	156436	39.707

Spareparts

	Art. No.	Type No.
Hose with quick connector, length 50 cm, G 1/4 swivelling	114538	38.250