


Straight push-in connector with plug nipple

stainless steel

STAINLESS STEEL

Art. No. 135287

Type No. 859.1008 ES



Exemplary illustration

For use in more aggressive environments and corrosive media.

Only recommended for use in combination with stainless steel quick connectors type 844 ff. Suitability testing for use with other series is the responsibility of the user.

Technical data

Working pressure	-0.98 - 20 bar
Operating temperature	-20 to 150 °C
Medium temperature	-20 to 150 °C
Material	Stainless steel 1.4404
Medium	Compressed air, corrosive media (if compatible with material)
Sealant	FPM
Applications	Compressed air syst., chemical and food, pharma, pack., vacuum
Version	Reducing
For tube O.D.	8 mm
L1	42.8 mm
Plug connection	10 mm
Suitable pipe materials	PVDF, PTFE, PA, PU

The suitability test for the use with alternative specifications is the user's responsibility.

Only recommended for use in combination with stainless steel quick connectors type 844 ff.


Commercial data

Customs tariff number	73072980
Country of origin	IN
eCl@ss 5.1.4	27294201
eCl@ss 9.0	27294201
UNSPSC_Code_v190501	27131613
UNSPSC_CodeDesc_v190501	Air coupling

Material informations

REACH SVHC1 substance name	no
CAS no. SVHC 1	no CAS No.
RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Dimensions



Plug connection	For tube O.D.	L1	D1
mm	mm	mm	mm
10	8	42.8	14.0

Accessories

	Art. No.	Type No.
Loosening tool, quick-connect fittings, hose exterior \varnothing 3 - 10 mm	108853	LW3-10
Loosening tool, quick-connect fittings, hose exterior \varnothing 4-14 mm	121863	LW4-14