

Flange pressure reducer



Art. No. 146762

Type No. FDM200.H2CH4H2COCH4.10



Exemplary illustration

Single-stage type in pressed brass version in accordance with DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauge each for cylinder content and working pressure.

Bottle pressure reducers are used to reduce a gas that has been compressed, liquefied and dissolved in a bottle at a certain filling pressure/upstream pressure to a much lower, as constant as possible back pressure/overpressure, as independently as possible of fluctuations in the upstream pressure and flow rate. Cylinder pressure reducers with connection to gas cylinders are suitable for reducing the pressure of various gases. They have a type approval in accordance with DIN EN ISO 2503 for welding, cutting and related processes. The connections are designed in accordance with DIN 477.

Technical data

Housing	Pressed brass
Min. temperature range	-20 °C
Max. temperature range	60 °C
Gas type	Hydrogen, methane, illuminating gas, natural gas
Colour code	rot
Min. working pressure	0 bar
Max. working pressure	10 bar
Cylinder connection	W21,80X1/14 LH <i>i</i>
Hose connection	G 3/8 LH
Display range working pressure gauge	0-16 / rZ 10 bar
Indicating range	0 - 300/400 bar

Areas of application: Mechanical engineering, electrical and automotive industry, welding technology

Commercial data

Customs tariff number	84811099
Country of origin	IT
eCl@ss 5.1.4	37011108
eCl@ss 9.0	37011108
UNSPSC_Code_v190501	41112404
UNSPSC_CodeDesc_v190501	Pressure regulator

Accessories

	Art. No.	Type No.
Pressure gauge housing protection cap mad of Plastic, black	146838	MGSK.KS.63
Pressure gauge double housing protecti. cap made of Plastic black	146839	MDGSK.KS.63
Protective bracket for Cylinder pressure regulator Black p. steel	146840	SBF.S
Protective caps for pressure gauge Ø 63, red	101301	GS 30
Protective caps for pressure gauge Ø 63, blue	101302	GS 31

Spareparts

	Art. No.	Type No.
Content pressure gauge f. Cylinder pressure reg., neut., 0-400bar	146825	IMF.N.14.400.63
Working pressure gauge f. Cylinder pressure reg., neutr., 0-16bar	146829	AMF.N.14.016.63
Replacement seal f. Cylinder pressure regulator(Cyl. con.)Plastic	146832	EDF.KS
Hose connector incl. nut, for hose I.D. 7.2/9/10/11.5	146837	STMF.38LH.MS