

Flange pressure reducer

Art. No. 146767 Type No. FDM200.FG.0-301



Exemplary illustration

Single-stage type in pressed brass version in accordance with DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauge each for cylinder content and working pressure.

Bottle pressure reducers are used to reduce a gas that has been compressed, liquefied and dissolved in a bottle at a certain filling pressure/upstream pressure to a much lower, as constant as possible back pressure/overpressure, as independently as possible of fluctuations in the upstream pressure and flow rate. Cylinder pressure reducers with connection to gas cylinders are suitable for reducing the pressure of various gases. They have a type approval in accordance with DIN EN ISO 2503 for welding, cutting and related processes. The connections are designed in accordance with DIN 477.

Technical data

Housing	Pressed brass
Min. temperature range	-20 °C
Max. temperature range	60 °C
Gas type	Forming gas
Colour code	schwarz
Cylinder connection	W21,80X 1/14 LHi
Hose connection	G 1/4
Indicating range	0 - 300/400 bar
Min. flowmeter	0 l/min
Max. flowmeter	30 l/min

Areas of application: Mechanical engineering, electrical and automotive industry, welding technology



Commercial data

Customs tariff number	84811099
Country of origin	IT
eCl@ss 5.1.4	37011108
eCl@ss 9.0	37011108
UNSPSC_Code_v190501	41112404
UNSPSC_CodeDesc_v190501	Pressure regulator

Accessories

	Art. No.	Type No.
Pressure gauge housing protection cap mad of Plastic, black	146838	MGSK.KS.63

Spareparts

	Art. No.	Туре No.
Content pressure gauge f. Cylinder pressure reg., neut., 0-400bar	146825	IMF.N.14.400.63
Flow meter for Cylinder pressure regulator, 0 - 30 l/min, MS/KS	146831	DFMF.30
Replacement seal f. Cylinder pressure regulator(Cyl. con.)Plastic	146832	EDF.KS
Hose connector incl. nut, for hose I.D. 6.5/7.2/9/9.8	146836	STMF.14LH.MS